

# Atlas Three Phase Inverter with Dual MPPT

RCM-3-TP-D/4-TP-D/5-TP-D/6-TP-D/  
8-TP-D/10-TP-D/12-TP-D/15-TP-D

**IP66  
PROTECTION**

**MAX  
EFFICIENCY  
98,3%**



**10  
YEAR FREE  
WARRANTY**



## High-efficiency

- Maximum efficiency is up to 98.3%
- Low startup voltage, ultrawide MPPT voltage range
- 200% oversizing, 110% overloading output (Except 15kW model)
- Built-in shadow tracking function



## Economic

- Ultra-high power density
- Support high power solar panel



## Smart

- Built-in export power control
- Remote setting and upgrading
- 24 hours operation monitoring
- Intelligent load management - heat pump (Optional)
- Multiple monitoring methods, WiFi V3.0 (Included) / LAN / 4G / WiFi V3.0 plus (Optional)



## TECHNICAL PARAMETERS

Model	RCM-3-TP-D	RCM-4-TP-D	RCM-5-TP-D	RCM-6-TP-D	RCM-8-TP-D	RCM-10-TP-D	RCM-12-TP-D	RCM-15-TP-D
<b>DC Input</b>								
Max. PV array input power [Wp]	6000	8000	10000	12000	16000	20000	24000	30000
Max. PV input voltage [V]	1000	1000	1000	1000	1000	1000	1000	1000
Startup voltage [V]	150	150	150	150	150	150	150	150
Nominal input voltage [V]	640	640	640	640	640	640	640	640
MPP tracker voltage range [V]	120~980	120~980	120~980	120~980	120~980	120~980	120~980	120~980
No. of MPP trackers/Strings per MPP tracker	2(1/1)	2(1/1)	2(1/1)	2(1/1)	2(1/1)	2(1/1)	2(2/1)	2(2/1)
Max. input current [A]	16/16	16/16	16/16	16/16	16/16	16/16	32/16	32/16
Max. short circuit current [A]	20/20	20/20	20/20	20/20	20/20	20/20	40/20	40/20
<b>AC Output</b>								
Nominal AC output power [W]	3000	4000	5000	6000	8000	10000	12000	15000
Nominal AC output current [A]	4.6/4.4	6.1/5.8	7.6/7.3	9.1/8.7	12.2/11.6	15.2/14.5	18.2/17.4	22.7/21.8
Max. AC output apparent power [VA]	3300	4400	5500	6600	8800	11000	13200	15000
Max. AC output current [A]	4.8	6.4	8.0	9.6	12.8	16.0	19.1	22.7
Nominal AC voltage [V]	220/380V, 230/400V, 3/N/PE							
Nominal grid frequency/ Grid frequency [Hz]	50/60							
Displacement power factor	0.8 leading-0.8 lagging							
THDi (Rated power) [%]	< 3							
<b>System Data</b>								
Max. efficiency [%]	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3
Euro efficiency [%]	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8
Standby consumption (night) [W]	<3							
Ingress protection	IP66							
Operating temperature range [°C]	-30~+60 (Derating above 45)							
Max. operation altitude [m]	4000 (Derating above 3000)							
Relative humidity [%]	0~100							
Typical noise emission [dB]	<30	<30	<30	<30	<45	<45	<50	<50
Storage temperature [°C]	-30~+60							
Dimensions (W×H×D) [mm]	342*434*144.5				342*434*156			
Weight [kg]	15.5	15.5	15.5	15.5	17	17	18	18
Cooling concept	Natural cooling				Smart fan cooling			
Communication interfaces	USB / RS485 / DRM / WiFi (Optional: LAN / 4G / WiFi V3.0 plus) / Adapter box (Optional)							
<b>Protection</b>								
Over/under voltage protection	YES							
DC isolation protection	YES							
DC reverse protection	YES							
Grid monitoring	YES							
DC injection monitoring	YES							
Back feed current monitoring	YES							
Residual current detection	YES							
Anti-islanding protection	YES							
Over temperature protection	YES							
SPD (DC/AC)	Type III / Type III							
<b>Standard</b>								
Safety	IEC/EN 62109-1; IEC/EN 62109-2; NB/T 32004							
EMC	IEC/EN 61000; NB/T 32004							
Certification	VDE4105; EN 50549; AS 4777.2; VDE4105; IEC 61727; IEC 62116; IEC 61683; IEC 60068; EN 50530; NB/T 32004							